P21328.A01

voids of the lower partial layer.

- 7. (Amended) A carriageway comprising a draining bituminous upper layer blanket, characterised in that the upper layer blanket complies with claim 1.
- 8. (Amended) A method of realisation of a draining bituminous upper layer blanket according to claim 1, characterized in that the upper and lower partial layers are applied in a single pass by a road finishing machine.
- 9. (Amended) A method of realisation of a draining bituminous upper layer blanket according to claim 1, characterised in that the upper and lower partial layers are applied in two successive passes by a road finishing machine.

REMARKS

Upon entry of the above amendment, claims 1-9 will remain pending, with claim 1 being in independent form. This Amendment is being filed simply to remove multiple dependency of claims.

P21328.A01

While a fee is not required, the Commissioner is hereby authorized to charge any required fees or refund excess payments to our Deposit Account No.19-0089.

Respectfully submitted, Jean-Paul MICHAUT

- Slewhom # 45,294

Neil F. Greenblum Reg. No. 28,394

August 14, 2001 GREENBLUM & BERNSTEIN, P.L.C. 1941 Roland Clarke Place

Reston, VA 20191 (703) 716-1191

Enclosures: Appendix 1

Appendix 2

APPENDIX 2

- 3. (Amended) A layer according to claim 1 [or 2], characterised in that the aggregate size distribution of the upper partial layer is selected among the 2/4, 4/6 and 6/10 ranges.
- 4. (Amended) A layer according to <u>claim 1</u> [one of the claims 1 to 3], characterised in that the aggregate size distribution of the lower partial layer is selected among the 10/14, 10/20 and 14/20 ranges.
- 5. (Amended) A layer according to <u>claim 1</u> [one of the claims 1 to 4], characterised in that both upper and lower partial layers have approximately the same void ratio.
- 6. (Amended) A layer according to <u>claim 1</u> [one of the claims 1 to 4], characterised in that both upper and lower partial layers have approximately the same void ratio and in that the average volume of the voids of the upper partial layer is smaller than the average volume of the voids of the lower partial layer.
- 7. (Amended) A carriageway comprising a draining bituminous upper layer blanket, characterised in that the upper layer blanket complies with <u>claim 1</u> [any of the claims 1 to 6].
- 8. (Amended) A method of realisation of a draining bituminous upper layer blanket according to <u>claim 1</u> [any of the claims 1 to 6], characterised in that the upper and lower partial layers are applied in a single pass by a road finishing machine.
- 9. (Amended) A method of realisation of a draining bituminous upper layer blanket according to <u>claim 1</u> [any of the claims 1 to 6], characterised in that the upper and lower partial layers are applied in two successive passes by a road finishing machine.

APPENDIX 1

ABSTRACT

A bituminous upper layer draining blanket comprising two partially superposed layers whereof the upper layer contains aggregate with low partiele-size distribution and a modified bituminous binder, and whereof the lower layer contains aggregate with high particle-size distribution and a bituminous binder, characterised in that the upper partial layer comprises an added filler material between 2 and 11% in weight.